



<<<TECHNICAL INFORMATION BULLETIN>>>

CADI-GLOSS

29% SOLIDS

ULTRA HIGH SOLIDS ACRYLIC URETHANE FLOOR FINISH

Ultra High Solids Unsurpassed "Wet Look" Institutional & Commercial Traffic

DESCRIPTION:

A premium, ultra-high solids floor finish for industrial, institutional and commercial heavy traffic applications. An exclusive blended system of very high solid acrylic co-polymers producing unsurpassed ultra-high gloss, clarity, and durability with outstanding anti-slip properties, detergent resistance and recoatability. Levels perfectly, dries quickly between coats and is non-yellowing. Internal plasticizers promote tremendous response to low, high and ultra-high speed burnishing. Perfect for use on most types of floor surfaces including linoleum, asphalt tile, vinyl, vinyl composition, sealed concrete, terrazzo, quarry tile and many others.

DIRECTIONS:

A PROPERLY MAINTAINED FLOOR IS ESSENTIAL FOR LONG LASTING PERFORMANCE AND BEAUTY.

APPLICATION:

1. Remove all excess soil with a concentrated cleaner
(For floors with a heavy finish build up, remove with a strong stripper)
2. Rinse and let dry
(If floor is porous, seal with a quality sealer as per directions)
3. Apply 2 to 3 thin uniform coats of floor finish
4. Allow each coat to dry thoroughly between applications, approximately 30 minutes dry time per coat

DAILY MAINTENANCE:

- Frequent dust mopping and daily damp mopping with a neutral cleaner
- May be spray-buffed or low, high or ultra-high speed burnished

FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY

**2219 E. UNIVERSITY DR., PHOENIX, ARIZONA 85034
TOLLFREE: (888) 874-2100 | FAX: (602) 957-2980**